

Stainless steel square mesh with opening size from 300 microns to 25mm.

The wire mesh was made according to the technical requirements ISO 9044 and ASTM E2016.

The materials of the wires for mesh are conforming to the requirements ASTM A580.

| Mesh No. | Wire Diameter | | Opening Size | | Open Area | Weave Type | Roll Width Max |
|----------|---------------|-------|--------------|-------|-----------|------------|----------------|
| | inch | mm | inch | mm | % | | mm |
| 70×70 | 0.0063 | 0.160 | 0.0080 | 0.203 | 31.3 | Plain | 2000 |
| 70×70 | 0.0059 | 0.150 | 0.0084 | 0.213 | 34.4 | Plain | 2000 |
| 80×80 | 0.0055 | 0.140 | 0.0070 | 0.178 | 31.3 | Plain | 2000 |
| 80×80 | 0.0051 | 0.130 | 0.0074 | 0.188 | 34.9 | Plain | 2000 |
| 80×80 | 0.0047 | 0.120 | 0.0078 | 0.198 | 38.7 | Plain | 2000 |
| 90×90 | 0.0047 | 0.120 | 0.0064 | 0.162 | 33.0 | Plain | 2000 |
| 100×100 | 0.0045 | 0.114 | 0.0055 | 0.140 | 30.4 | Plain | 2000 |
| 100×100 | 0.0040 | 0.102 | 0.0060 | 0.152 | 35.8 | Plain | 2000 |
| 100×100 | 0.0035 | 0.089 | 0.0065 | 0.165 | 42.2 | Plain | 2000 |
| 110×110 | 0.0028 | 0.070 | 0.0063 | 0.161 | 48.6 | Plain | 2000 |
| 110×110 | 0.0035 | 0.090 | 0.0055 | 0.141 | 37.2 | Plain | 2000 |
| 120×120 | 0.0035 | 0.090 | 0.0048 | 0.122 | 33.0 | Plain | 2000 |
| 124×124 | 0.0031 | 0.080 | 0.0049 | 0.125 | 37.1 | Plain | 2000 |
| 150×150 | 0.0024 | 0.060 | 0.0043 | 0.109 | 41.7 | Plain | 2000 |
| 150×150 | 0.0028 | 0.071 | 0.0039 | 0.098 | 33.7 | Plain | 2000 |
| 154×154 | 0.0026 | 0.065 | 0.0039 | 0.100 | 36.7 | Plain | 2000 |
| 160×160 | 0.0021 | 0.053 | 0.0042 | 0.106 | 44.4 | Plain | 2000 |
| 170×170 | 0.0022 | 0.055 | 0.0037 | 0.094 | 39.9 | Plain | 2000 |
| 180×180 | 0.0021 | 0.053 | 0.0035 | 0.088 | 39.0 | Plain | 2000 |
| 190×190 | 0.0022 | 0.055 | 0.0031 | 0.079 | 34.6 | Plain | 2000 |
| 194×194 | 0.0024 | 0.060 | 0.0028 | 0.071 | 29.3 | Plain | 2000 |
| 200×200 | 0.0020 | 0.050 | 0.0030 | 0.077 | 36.8 | Plain | 2000 |
| 200×200 | 0.0022 | 0.055 | 0.0028 | 0.072 | 32.1 | Twill | 2000 |
| 250×250 | 0.0016 | 0.040 | 0.0024 | 0.062 | 36.8 | Twill | 2000 |
| 265×265 | 0.0016 | 0.040 | 0.0022 | 0.056 | 34.0 | Twill | 2000 |
| 270×270 | 0.0016 | 0.040 | 0.0021 | 0.054 | 33.0 | Twill | 2000 |
| 300×300 | 0.0016 | 0.040 | 0.0018 | 0.045 | 27.8 | Twill | 2000 |
| 325×325 | 0.0012 | 0.030 | 0.0019 | 0.048 | 38.0 | Plain | 2000 |
| 325×325 | 0.0014 | 0.036 | 0.0017 | 0.042 | 29.1 | Twill | 2000 |
| 325×325 | 0.0014 | 0.036 | 0.0017 | 0.043 | 29.6 | Twill | 2000 |
| 360×360 | 0.0013 | 0.032 | 0.0015 | 0.039 | 29.9 | Twill | 2000 |
| 400×400 | 0.0012 | 0.030 | 0.0013 | 0.034 | 27.8 | Twill | 1600 |
| 500×500 | 0.0010 | 0.025 | 0.0010 | 0.025 | 25.0 | Twill | 1500 |
| 635×635 | 0.0008 | 0.020 | 0.0008 | 0.020 | 24.3 | Twill | 1300 |

Any interest, please feel free to contact us!

Dashang Wire Mesh

Email: sales@dashangmesh.com

Tel/Fax: 0086 318 7563319/7521333

Pho: 0086 18632807688

Industrial Woven Wire Mesh Solution!

